

Material Safety Data Sheet



MSDS #: 50080

24-Hour Emergency Telephone Number
1-800-424-9300 (Chemtree)MSDS #: 50080
DATE OF PREPARATION: 8/26/2006
LAST REVISION DATE: 4/30/2001**HMIS Ratings:**HEALTH: 3
FLAMMABILITY: 1
REACTIVITY: 1
PROTECTION: J**SECTION I - PRODUCT IDENTIFICATION**

PRODUCT NAME: CROSSLINKER

PRODUCT DESCRIPTION: POLYFUNCTIONAL AZIRIDINE CROSSLINKER

SECTION II - HAZARDOUS INGREDIENTS

INGREDIENT	CAS #	% WEIGHT	Occupational Exposure Limits		VAPOR PRESSURE- mm Hg
			ACGIH-TLV	OSHA-PEL	
POLYFUNCTIONAL AZIRIDINE	64265-57-2	100%	N/E	N/E	N/E

SECTION III - PHYSICAL DATA

BOILING RANGE: N/E

EVAPORATION RATE: Slower than n-Butyl Acetate

% VOLATILE - WT: <0.5

DENSITY: 8.90 LBS/GAL (1.07KG/L)

VAPOR DENSITY: Heavier than air

SOLUBILITY IN WATER: Miscible

PRODUCT CHARACTERISTICS: Thick, amber liquid with rank odor

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION: Non-Flammable

FLASH POINT: Over 200F (93C) PMCC

% OF VOL. OF FLAMMABLE LIMITS (Upper): N/E

(Lower): N/E

EXTINGUISHING MEDIA: Foam, Carbon Dioxide, Dry Chemical, Water Fog

UNUSUAL FIRE - EXPLOSION HAZARDS: Material in itself is normally stable, but can become unstable at elevated temperatures and pressures, or may react with water with some release of energy, but not violently.

SPECIAL FIREFIGHTING PROCEDURES: Water may be used to cool closed containers to prevent pressure build-up. Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes.