

Bona Sport[®] CourtLines[®]



DESCRIPTION:

CourtLines[®] is a high-solids, fast-drying, solvent-based graphic arts sport paint, manufactured specifically for use with both waterborne and oil-modified sport floor sealers and finishes. Available in fifteen vibrant primary colors, all CourtLines[®] paints are all blendable to achieve an endless array of custom colors.

FEATURES:

- Specifically formulated for sport game lines, lettering, and logos
- Use with Bona[®] waterborne or oil-modified finishes
- 15 vibrant colors, blendable for an unlimited possibility of custom colors
- Fast drying with 24 hour recoat
- VOC compliant
- Very low odor—does not contain Xylene
- High solids
- Low viscosity
- Excellent flow and leveling
- Available in quarts

RECOMMENDED USE:

- Basketball courts
- Volleyball courts
- Racquetball, squash and badminton courts
- Multi-purpose gym, stage, aerobic and dance floors

DIRECTIONS FOR USE:

BEFORE USING, READ ALL DIRECTIONS AND MATERIAL SAFETY DATA SHEET #65020 FOR WHITE AND #65010 FOR ALL OTHER COLORS. THIS PRODUCT IS NOT INTENDED FOR APPLICATION TO WALLS, CABINETS, OR OTHER VERTICAL SURFACES.

Use directly from the can, do not thin. Non-photochemically reactive (not an ozone precursor). BONA COURTLINES® is specifically designed for use with BONA SPORT® waterborne or oil-modified finishing systems on wood sport floors. COURTLINES® paints are blendable to achieve any custom color desired. Blending, rather than tinting, maintains brightness and application characteristics.

PREPARATION:

1. Sand and prepare floors using accepted MFMA procedures. All old finish should be removed to ensure proper adhesion.
2. Sweep, vacuum, and tack floor as recommended. 3. Apply game lines in accordance with sealer and finish instructions.

Application

1. Before application, thoroughly abrade entire floor with a 120 grit screen. Make sure paint is applied the same day the floor is abraded. 2. Tape gym lines according to MFMA specifications. 3. Stir paint thoroughly. 4. Apply evenly with the grain of the wood, using a brush or 1/4" nap roller. Apply a thin coat of paint at a rate of 500-600 sqft/gallon. More than one coat may be needed. Apply second coat once first coat is dry to the touch (1-4 hours). 5. Allow paint to dry 24 hours before coating with finish. Additional dry time may be needed in cooler temperatures and high humidity. 6. Abrade the entire floor with a Bona® Conditioning Pad (or a used 120 or 150 screen). Sweep, vacuum, and tack with water. Allow floor to dry 30 minutes prior to applying finish. If coating or applying game lines more than 24 hours after abrading, floor must be re-abraded to ensure adhesion of finish.

Note: If using blue tape, it is not necessary to remove tape in between paint applications; paint will not bleed under tape or pull up when tape is removed if tape is properly applied.

Note: When working with more than one container of the same color, intermix to ensure uniformity. When mixing "custom" colors, mix enough paint to cover entire job to ensure uniformity.

Coverage: Approximately 500-600 square feet per gallon (125-150 square feet per quart).

Clean-Up: Clean application tools and equipment with mineral spirits.

Ingredients: Alkyd resins, odorless mineral spirits, pigments, driers, titanium dioxide.

OSHA Class II (Combustible Liquid). Flashpoint: 100° F (TCC)

Stability: One year shelf life in unopened container.

Storage: Keep container closed when not in use. Do not transfer contents to other containers for storage and disposal. To avoid contamination, do not mix used material into unused material. In case of spillage, absorb with inert material. Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

DANGER: RAGS, STEEL WOOL OR WASTE SOAKED WITH COURTLINES® MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER EACH USE, PLACE RAGS, STEEL WOOL OR WASTE IN A SEALED, WATER-FILLED METAL CONTAINER.

SPECIFICATIONS/PHYSICAL DATA:

Physical Characteristics:

Ingredients - Alkyd resins, odorless mineral spirits, pigments, driers, titanium dioxide

Base Colors - Red, yellow, green, lt. blue, dark blue, orange, brown, black, white, gold, maroon, purple, lt. beige, gray, NC blue

Odor - Non-offending low odor

Solids - Colors: 47-51%; White: 66%

Flash Point - 100° F (TCC)

Viscosity - 60-70KU (Stormer @ 25°C)

Packaging - 1-quart cans

Density - Colors: 7.6-7.9 lbs./gallon; White: 11.1 lbs./gallon

VOC - Does not exceed 490 grams per liter (4.1 pounds per gallon)

Stability - One year shelf life in unopened container

Application Characteristics:

Coverage - 500-600 sq. ft. per gallon (125-150 square feet per quart)

Leveling - Excellent

Drying Time - 24 hour recoat

Application Tools - Brush, roller

Bona US

303/371-1411 • FAX 303/371-6958 • 800/872-5515 • www.bona.com
Item #2988 © 03/09 Bona US